

3D VISUALISATION ONLY




NORTH BRISTOL CONVERSIONS

COMPLETE CARPENTRY CONSTRUCTION







Permitted development rules - Loft

- -Materials must be similar in appearance to the existing house.
- -Volume of enlargement (including any previous enlargement) must not exceed the original roof space by more than: 40 cubic metres for terraced houses; Proposed volume is 25.9sqm cubic meters
- -Must not exceed the height of the existing roof
- On the principal elevation of the house (where it fronts a highway), must not extend beyond the existing roof slope.
- -Side-facing windows must be obscure-glazed; and, if opening, to be 1.7 metres above the floor of the room in which they are installed. Construction must ensure that:
- -The eaves of the original roof are maintained (or reinstated)
- -Any enlargement is set back, so far as practicable, at least 20cm from the original eaves
- -The roof enlargement does not overhang the outer face of the wall of the original house With the exceptions that:
- -Points 1 and 2 do not apply to the relevant parts of any hip-to-gable enlargement -None of these three points apply to the relevant parts of any enlargement that joins the original roof to the roof of a side or rear extension.

LOFT VOLUME CALCULATON


A = 8.5 B = 2.515 C = 2.427 Base = (B x C) \div 2 Volume = base x A

Total 25.9m3

05.01 - SECTION AA

05.02 - **SECTION BB**

ALL STRUCTURAL ELEMENTS TBC BY ENGINEER



06.01 - SECTION CC

Permitted development rules - Loft

- -Materials must be similar in appearance to the existing house.
- -Volume of enlargement (including any previous enlargement) must not exceed the original roof space by more than: 40 cubic metres for terraced houses; Proposed volume is 25.9sqm cubic meters
- -Must not exceed the height of the existing roof
- On the principal elevation of the house (where it fronts a highway), must not extend beyond the existing roof slope.
- -Side-facing windows must be obscure-glazed; and, if opening, to be 1.7 metres above the floor of the room in which they are installed.

Construction must ensure that:

- -The eaves of the original roof are maintained (or reinstated)
- -Any enlargement is set back, so far as practicable, at least 20cm from the original eaves
- -The roof enlargement does not overhang the outer face of the wall of the original house With the exceptions that:
- -Points 1 and 2 do not apply to the relevant parts of any hip-to-gable enlargement -None of these three points apply to the relevant parts of any enlargement that joins the original roof to the roof of a side or rear extension.

LOFT VOLUME CALCULATON

A = 8.5 B = 2.515 C = 2.427Base = $(B \times C) \div 2$ Volume = base x A

Total 25.9m3

DRAFT ISSUE